


3211/3221 Series Accumulating Conveyor Roller




3211/3221 Series Steel Single/Double Sprocket Accumulating Roller

Product Features

- With typical friction driven accumulation, the accumulation force is associated to duty capacity.
 - The bearing end cap consists of a precision ball bearing, a polymer housing and end cap seal. Combined they provide an attractive, smooth and quite running roller.
 - The design of the end cap protects the bearings by providing excellent resistance to dust and splashed water.
 - Utilizes durable, steel sprockets.
 - Standard configuration with anti-static design surface impedance $\leq 10^6 \Omega$.
 - Temperature range: $-5^{\circ}\text{C} \sim +40^{\circ}\text{C}$.
 - Humidity range: 30%~ 90% RH (non-condensation).
- Please contact us if humidity out of this scope.

Specifications


Bearing Unit	
Bearing housing	Polyamide, black
End cap	Polypropylene, Damon green
Precision ball bearing	6002
Drive Element	
Sprocket	Steel



3211 Series Internal Thread

Tube Dia.(D)	Shaft Dia.(d)		Sprocket Type	A	C	d1
Φ50	Φ12/15	BF/L=W+41	08B14T	17	18.5	57.07
Φ60	Φ12/15	BF/L=W+41	08B14T	17	18.5	57.07

Tube	D*T	Shaft Dia.(d)	
		Φ12 (M8x15)	Φ15 (M10x20)
Steel, zinc plated	Φ50x1.5	3.211.SH.C.ACC	3.211.SH.C.ADC
	Φ60x2.0	3.211.SOC.ACC	3.211.SOC.ADC
Stainless steel (304)	Φ50x1.5	3.211.NHC.BCC	3.211.NHC.BDC
	Φ60x2.0	3.211.NOC.BCC	3.211.NOC.BDC



3221 Series Internal Thread

Tube Dia.(D)	Shaft Dia.(d)		Sprocket Type	A	B	C	d1
Φ50	Φ12/15	BF/L=W+63	08B14T	17	22	18.5	57.07
Φ60	Φ12/15	BF/L=W+63	08B14T	17	22	18.5	57.07

Tube	D*T	Shaft Dia.(d)	
		Φ12 (M8x15)	Φ15 (M10x20)
Steel, zinc plated	Φ50x1.5	3.221.SH.C.ACC	3.221.SH.C.ADC
	Φ60x2.0	3.221.SOC.ACC	3.221.SOC.ADC
Stainless steel (304)	Φ50x1.5	3.221.NHC.BCC	3.221.NHC.BDC
	Φ60x2.0	3.221.NOC.BCC	3.221.NOC.BDC